

Equipment

Designation	Part number
- PTFE + FEP (Encapsulated O-Ring: Teflon like properties over Viton or Silicone)	SE=02
- PU (Polyurethane)	SE=06
- Stainless Steel + Carbide	MA=SC
- PTFEG (PTFE + Graphite compound)	SE=05
- PTFE - Polytetrafluorothylene (Teflon like properties)	SE=01
- Motor 9000 (30:1)	MO=90
- Leather	SE=04
- PE - Polyethene (UHMWPE)	SE=03
- Follower plate (Ø=105mm)	FO=FP
- Stainless Steel	MA=SS
- Mixed Materials	MA=CS
- Motor 7000 (18:1)	MO=70
- PEEK/PTFEG (PTFE + Glass compound)	SE=07
- Motor 6000 (30:1)	MO=60
- Wall mounted (Inlet F 1-1/2" BSPP)	FO=WM



REXSON 2B0588

2 Ball Pump

Pumping beyond possible.

Product highlights

- Robust and reliable
- Simple to maintain
- Configurable and versatile



Additional information

- User manual
- Spare parts
- Accessories
- Documents
- Videos



Sames
45001 Five Mile Road
Plymouth, MI 48170 - USA
Phone: +1 734 979 0100
www.sames.com

Sames
931 Progress Ave, Unit 7
Scarborough, Ontario M1G 3V5
CANADA
Phone: +1 800 450 0655



Sames reserves the right to modify its equipment or specifications without further notice.
Document, products and pictures shown are not contractual.
09/2026

BOND • PROTECT • BEAUTIFY

www.sames.com

REXSON 2B0588

2 Ball Pump

This High Viscosity Pump is a 2 ball double-acting piston technology is used for Airless and extrusion application requiring medium flow rates.



Adapted industrial markets



ACE*



Automotive



Energy



Industrial



Railways



Transportation



Technical data table

Designation	Value	Unit
Maximum Air Pressure	6 (87)	bar (psi)
Pump displacement	588 (35.90)	cc/cycle (in^3/cycle)
Fluid Output at 15 cycles / mn	8,82 (2.33)	l/min (gal/min)
Fluid Output at 20 cycles / mn	11,76 (0.20)	l/min (gal/min)
Fluid Output at 60 cycles / mn	35,28 (9.32)	l/min (gal/min)
Maximum Material Pressure	180 (2600)	bar (psi)
Maximum Temperature	80 (176)	°C (°F)
Air Inlet Fitting	3/4"BSP(F)	
Material Inlet Port	105mm 1-1/2"BSP(F)	
Material Outlet Port	1-1/2"BSPT(F)	

Marking

Product	Type
REXSON 2B0588	CE 0080

*: "AgricultureConstruction and Earthmoving"



Technologies



2 Ball



Description

The REXSON pumps of the high viscosity range have been designed with robustness in mind, and the aim of offering a high degree of modularity to follow your application. Unlike liquid fluid pumping, the high viscosity range imposes highly variable mechanical stresses from one product to another.

Double-acting ball pumps are similar in construction to pumps for liquid products and are capable of transferring fluid up to 50,000 Cps. These pumps have been adapted for high viscosity products by optimizing the passage diameters, the nature of the seals, and the hardness of the materials.

To create your own pump that will meet your application specifications, you will have to select:

The correct air motor according to the maximum pressure,

The construction materials according to the nature of the product,

The foot and mounting style according to the product packaging, and your installation

The Seal pack (see the Documents tab to get all necessary information on our website).

Our air motors are designed for maximum airflow with a pilot distributor to allow fast inversion. They are equipped with a broad silencer to avoid water freezing at the motor outlet and can be controlled (start / stop) from a remote air control.

These pumps are used as feeding equipment directly from the product packaging in-wall mounting or installed on an elevator with a follower plate for open drums.

Performances

M1 Power distributor: Wide passageway for maximum airflow

L1 Upper Body: The upper part of the pump is of robust construction and must be able to withstand the maximum pressures.

L2 Upper Valve: This valve allows material to pass from the lower chamber to the upper chamber of the pump. It is designed to limit pressure loss.

L3 Lower Valve: This valve is essential for the suction of the product. It is designed to be as wide as possible for easy filling.

Productivity

M2 The Cover: Very easy to remove and to access the repair parts

M3 The Pulse Output: The motor can be easily monitored thanks to an air pulse occurring at each reversal.

L4 Motor adaptation flange: Unique and robust assembly of the motor shaft connection to the pump shaft. Allows quick adaptation to different air motors to vary the pressure ratio of the pump.

L5 Guard: To guarantee the safety of the operators, this guard prevents contact with the moving shaft of the pump.

L6 Lower Body: The pump lower is adapted as needed to be fixed on a follower plate, immersed in a bung drum, or simply threaded for connection to a manifold.

Sustainability

M4 Brass guiding ring: Enduring and accurate guidance system

M5 Camshaft inversion system: Very reliable reversal system

L7 Upper seals packing: Our pump range has a wide range of seal materials to suit all your needs.

L8 Rod and Cylinder: The piston shaft and the cylinder are made of triple chrome steel to ensure excellent abrasion resistance.

