

Equipment

Designation	Part number
- Wall mounted (Inlet/Outlet (F) 1" BSP)	FO=G1
- Motor 9200 (30:1)	MO=92
- PEEK/PTFEG (PTFE + Glass compound)	SE=07
- PU (Polyurethane)	SE=06
- Stainless Steel	MA=SS
- Motor 7200 (18:1)	MO=72
- Mixed Materials	MA=CS



REXSON 4B570

Quatro 4 Ball Pump

Pumping beyond possible.

Product highlights

- Robust and reliable
- Simple to maintain
- 3-in-1 functions: Booster, circulating and dosing



Additional information

- User manual
- Spare parts
- Accessories
- Documents
- Videos



Sames
45001 Five Mile Road
Plymouth, MI 48170 - USA
Phone: +1 734 979 0100
www.sames.com

Sames
931 Progress Ave, Unit 7
Scarborough, Ontario M1G 3V5
CANADA
Phone: +1 800 450 0655



Sames reserves the right to modify its equipment or specifications without further notice.
Document, products and pictures shown are not contractual.
09/2026

BOND • PROTECT • BEAUTIFY

www.sames.com

REXSON 4B570

Quatro 4 Ball Pump

This High Viscosity Pump is a 4 ball double-acting piston technology is used for booster, circulation and dosing applications that require medium to High flow rates.



Adapted industrial markets



Automotive



ACE*



Railways

Technical data table


Designation	Value	Unit
Maximum Air Pressure	6 (87)	bar (psi)
Pump displacement	570 (34.80)	cc/cycle (in^3/cycle)
Fluid Output at 15 cycles / mn	8,55 (2.25)	l/min (gal/min)
Fluid Output at 20 cycles / mn	11,40 (3.01)	l/min (gal/min)
Fluid Output at 60 cycles / mn	34,20 (9.03)	l/min (gal/min)
Maximum Material Pressure	300 (4350)	bar (psi)
Maximum Temperature	60 (140)	°C (°F)
Air Inlet Fitting	3/4"BSP(F)	
Material Inlet Port	1"BSP(F)	
Material Outlet Port	1"BSP(F)	

Marking

Product	Type
REXSON 4B570	CE 0080

*: "AgricultureConstruction and Earthmoving"

Technologies



4 Ball Quatro

Description

The REXSON pumps of the high viscosity range have been designed with robustness in mind, and the aim of offering a high degree of modularity to follow your application. Unlike liquid fluid pumping, the high viscosity range imposes highly variable mechanical stresses from one product to another. Double-acting ball pumps are similar in construction to pumps for liquid products and are capable of transferring fluid up to 50,000 Cps. These pumps have been adapted for high viscosity products by optimizing the passage diameters, the nature of the seals, and the hardness of the materials.

To create your own pump that will meet your application specifications, you will have to select:

The correct air motor according to the maximum pressure,

The construction materials according to the nature of the product,

The foot and mounting style according to the product packaging, and your installation

The seal pack (see the Documents tab to get all necessary information on our website).

Our air motors are designed for maximum airflow with a pilot distributor to allow fast inversion. They are equipped with a broad silencer to prevent water freezing at the motor outlet and can be controlled (start / stop) from a remote air control.

These pumps are wall mounted and require a material supply. They are designed to boost pressure or circulate material. Works well with spraying, extruded, streamed and dosing systems.

Performances

- M1 Power distributor: Large passageway for maximum airflow
- L1 Upper Body: The upper part of the pump is of robust construction and must be able to withstand the maximum pressures.
- L2 Material Piston: Moves the material in and out of the pump. The pump is balanced so there is equal pressure when the pump changes direction.
- L3 Ball Checks: All four checks are interchangeable and use a spring to minimize pump pulsation.

Productivity

- M2 The Cover: Very easy to remove and to access the repair parts
- M3 The Pulse Output: The motor can be easily monitored thanks to an air pulse occurring at each reversal.
- L4 Motor adaptation flange: Unique and robust assembly of the motor shaft connection to the pump shaft. Allows quick adaptation to different air motors to vary the pressure ratio of the pump.
- L5 Guard: To guarantee the safety of the operators, this guard prevents contact with the moving shaft of the pump.
- L6 Lubricator Cup: Includes lubricator cups for each rod seal ensures long lasting seals and isolates them from environmental reactive materials.

Sustainability

- M4 Brass guiding ring: Enduring and accurate guidance system
- M5 Camshaft inversion system: Very reliable reversal system
- L7 Upper / Lower seals packing: Our pump range has a wide range of seal materials to suit all your needs.
- L8 Rod and Cylinder: The piston shaft and the cylinder are made of triple chrome steel to ensure excellent abrasion resistance.

