

Equipment

Designation	Part number
05C3700 bare pump	472253400202
05C3700 bare pump	472253400102
05C3700 bare pump	472253400203
05C3700 bare pump	472253400101
05C3700 bare pump	472253400303
05C3700 bare pump	472253400103
05C3700 bare pump	472253400201
05C3700 bare pump	472253400401
05C3700 bare pump	472253400403
05C3700 bare pump	472253400301
05C3700 bare pump	472253400402
05C3700 bare pump	472253400302



PCS 05C3700 Quatro Airspray Paint Circulating System Pump

Airspray Paint Circulating System Pump

Product highlights

- Special design to pump high viscosity material: Oil, grease, adhesive and sealants
- Cup technology: Easy lubrication
- Modular conception: Easy maintenance and servicing



Additional information

- User manual
- Spare parts
- Accessories
- Documents
- Videos



Sames
45001 Five Mile Road
Plymouth, MI 48170 - USA
Phone: +1 734 979 0100
www.sames.com

Sames
931 Progress Ave, Unit 7
Scarborough, Ontario M1G 3V5
CANADA
Phone: +1 800 450 0655



Sames reserves the right to modify its equipment or specifications without further notice.
Document, products and pictures shown are not contractual.
09/2026

BOND • PROTECT • BEAUTIFY

www.sames.com

PCS 05C3700 Quatro Airspray Paint Circulating

Airspray Paint Circulating System Pump

4 ball low pressure pump for mixing room optimization



Adapted industrial markets

Technical data table

Designation	Value	Unit
Maximum Air Pressure	6 (87)	bar (psi)
Free Flow Rate	222 (58.60)	l/min (gal/min)
Height	1551 (610.60)	mm (in)
Width/depth	282 (111)	mm (in)
Depth	400 (157.50)	mm (in)
Maximum Material Pressure	30 (434.8)	bar (psi)
Air Consumption at 15 cycles / mn at 4 bar (60 psi)	72 (42.40)	m3/h (cfm)
Weight	113 (249.1)	kg (lbs)
Maximum Temperature	80 (176)	°C (°F)
Air Inlet Fitting	M 3/4" G	

Marking

Product	Type
---------	------

Technologies

Description

PCS 05C3700 Quatro 4 ball pump ensures strong pumping even for viscous material.

Performances

- Quiet air motor with no icing effect
- Low shear due to special design of paint passage, seats & balls

Productivity

- Separate air command 87 psi (6 bar) to run pump from 7 psi (0.5 bar) prevents air motor stalling

Sustainability

- Easy maintenance
- Wide variety of cartridges designed for easy replacement: PE, PE+PTFE & PE + Leather